



The MOVE wheelchair meets all Motion Composites lightness and quality objectives while remaining the most accessible folding wheelchair in our product line. We apply the latest technologies to offera standard wheelchair that will enhance yourday-to-day life with superior-quality parts for unrivaled toughness and performance. World-renowned, Motion Composites uses its knowhow and its passion for innovation to design unique, cutting-edge products inspired by you. As a visionary and passionate company, our ambition is driven by your experience. We believe that high-performance wheelchairs enhance people's lives with components, design, features and quality. MOVE is our passion for performance, our commitment to quality andour vision of greater freedom brought to life.

GO BEYOND!



### Move





# LIGHT AND WELL DESIGNED

- Agile and comfortable handling
- · Everything you need, right where you need it

The MOVE model was designed to offer efficiency and mobility at an affordable price. Thanks to its ingenious design, with components and accessories

carefully selected by our experts, the MOVE is one of the lightest standard wheelchairs on the market.

# SIMPLE AND EFFICIENT

Better configuration, greater mobility

Innovative armrests

The MOVE is a well-built adjustable wheelchair equipped with highly functional components.

The lightweight composite armrests easily convert from flip-back to single post and can be just as eas-

lly

adjusted for height. The MOVE adapts to your life and fulfills our mission: to increase your mobility.



## STURDY AND DURABLE

- More reliable for greater performance
- A durable, superior-quality wheelchair

The rigid unibody frame eliminates joints, reduces movement and maximizes efficiency. Solid design and reliable components that give you more. From flip-back convertible armrests to integrated push handles and Newton One spoke wheels, the MOVE offers excellent durability, serving you for many years to come.

### OPTIMAL SEAT-TO-FLOOR HEIGHT

- Practical contact with the ground, no matter the height
- Multiple heights thanks to the hybrid frame design

The frame's innovative design allows you to achieve a super-low 13-inch (33-cm) front seat-to-floor height. In addition to easier contact with the floor, this feature provides better foot propulsion if needed.





### **Features**

## RIGID UNIBODY FRAME

Eliminates joints, reduces movement and maximizes efficiency







INTEGRATED PUSH HANDLES

For added strength and durability

2



HYBRID FRAME DESIGN

Eliminates the need for both hemi and standard frame, while providing a complete range of seat-to-floor heights 3



ALUMINUM SEAT RAIL

With integrated seat slider for better seat sling support





ULTRARIGID FOLD-ING SYSTEM

Offers best-in-class propulsion efficiency

5



ANTI-FLUTTER SYSTEM

Provides a smooth, more efficient ride



### **Specifications**

FRAME	Folding
MATERIAL	6061 aluminum
TRANSPORT WEIGHT	14.0 lb. I 6.4 kg (16 x 16 without rear wheels, wheel locks, armrests, cushion, anti-tippers and footrest)
LIGHTEST CONFIGURATION	24.0 lb. I 10.9 kg with wheel locks and wheels
WEIGHT LIMIT	265 lb. l 120 kg 350 lb. l 159 kg—HD Kit
WIDTH	14 in. to 20 in. I 35.6 cm to 50.8 cm 18 in. to 22 in. I 45.5 cm to 55.9 cm—HD Kit
DEPTH	16 in. to 20 in. I 40.6 cm to 50.8 cm
FRONT SEAT-TO-FLOOR HEIGHT	12½ in. to 20½ in. I 31.8 cm to 52.1 cm (with 4 in. to 8 in. caster)
REAR SEAT-TO-FLOOR HEIGHT	12 in. to 20 in. I 30.5 cm to 50.8 cm (with 20 in. to 26 in. wheel)

### **Technologies**



#### **RIGID UNIBODY FRAME**

A unibody frame is much stronger and requires less maintenance than a standard two-part frame. It also reduces weight while maximizing propulsion efficiency



#### **ULTRARIGID FOLDING SYSTEM**

High-precision tolerances and oversized pivot axles for best-in-class propulsion efficiency.



#### **VERTICAL AXLE PLATE**

Offers two center of gravity positions, both in front of the back post, for optimal efficiency. Vertical mounting maximizes rigidity and responsiveness.



#### FLIP-BACK CONVERTIBLE ARMREST

Easy to adjust and made of composite materials for strength and reduced weight. It is the only armrest that converts from flip-back to single post without



#### **ANTI-FLUTTER SYSTEM**

Minimize flutter with a simple twist of a screw



#### **NEWTON ACCESSORIES**

Parts and accessories designed to be lighter with improved functionality.

### **Dimensions**



**SEAT WIDTH**14 in. to 22 in. I 35.6 cm to



BACK HEIGHT 16 in., 18 in., 20 in., 24 in. 40.6 cm, 45.7 cm, 50.8 cm, 61 cm



WHEEL CAMBER



**SEAT DEPTH** 16 in. to 20 in. I 40.6 cm to 50.8 cm



ARMREST HEIGHT 6 in. to 14 in. I 15.2 cm to 35.6 cm



CENTER OF GRAVITY 3/4 in. to 2 in. I 2 cm to 5.1 cm



FRONT SEAT-TO-FLOOR HEIGHT

12½ in. to 20½ in. I 31.8 cm



**FOOTREST ANGLE** 60°, 70°



OVERALL WIDTH

20% in. min. to 33% in. max. 52.7 cm min. to 85.1 cm max.



REAR SEAT-TO-FLOOR HEIGHT

12 in. to 20 in. I 30.5 cm to 50.8 cm



90° to 110°



**WEIGHT LIMIT** 265 lb. l 120 kg 350 lb. l 159 kg—HD Kit



